



12 inch



16 inch



20 inch

## Description

Affordable, durable horns for demanding sound reinforcement applications. The re-entrant style horn flare design provides an expansion path that is longer than conventional straight horns; this ensures that the lowest possible frequency response can be achieved. The Professional PA horns are formed from lightweight aluminum and painted with a durable polyester finish, so you know that they will survive years of exposure to sun and rain. Great for indoor or outdoor applications, sturdy mounting yoke for precise alignment included. Standard 1-3/8"-18 threaded throat.

Please consider the following features:

- Excellent low-mid frequency response
- Weatherproof aluminum construction
- Steel hardware for long service life
- For indoor or outdoor applications
- Standard 1-3/8"-18 threaded throat

Technical data	HN12-2	HN14-2	HN16-2	HN18-2	HN20-2
Horn diameter	31 cm	36.5 cm	41 cm	47 cm	51 cm
Horn Length	25 cm	28 cm	28 cm	32 cm	36 cm
Low frequency cutoff	180 Hz	190 Hz	220 Hz	210 Hz	200 Hz
Horn material	aluminium	aluminium	aluminium	aluminium	aluminium
Colour	grey	grey	grey	grey	grey
Connecting thread	1 3/8", international	1 3/8", international	1 3/8", international	1 3/8", international	1 3/8", international