

10W



Technical data	HWR121T
Load rating at 100V	10W
Transformer tapings	10W (100V)
Frequency range	110-16KHz
SPL(@1W/m)	92dB
Speaker Ø and Impedance	2×5" / 8 ohms
Dimension H×W×D(mm)	213×290×130mm
Material,Colour	ABS , white

10W



Technical data	HWR124T
Load rating at 100V	10 W
Transformer tapings	10-5-2.5W (100V)
Frequency range	110-20KHz
SPL(@1W/m)	92dB
Speaker Ø and Impedance	6 1/2" / 8 ohms
Dimension H×W×D(mm)	213×210×95mm
Material,Colour	steel , white

6W



Technical data	HWR125T
Load rating at 100V	6W
Transformer tapings	6-3-1.5W (100V)
Frequency range	110-16KHz
SPL(@1W/m)	90dB
Speaker Ø and Impedance	5" / 8 ohms
Dimension H×W×D(mm)	208×138×130mm
Material,Colour	wood , white or black

6W



Technical data	HWR126T
Load rating at 100V	6W
Transformer tapings	6-3-1.5W (100V)
Frequency range	110-16KHz
SPL(@1W/m)	90dB
Speaker Ø and Impedance	5" / 8 ohms
Dimension H×W×D(mm)	200×200×85mm
Material,Colour	wood , white or black