

10W



Horn Speaker, with 100 V transformer H-10TA

15W



Horn Speaker, with 100 V transformer H-15TA

30W



Horn Speaker, with 100 V transformer H-30TA

Description

Very stable and attractive horn speaker with integrated 100V matching transformer. This series is of high-quality plastic and therefore shock- and scratch-resistant.

The horn speakers H-10TA, H-15TA and H-30TA in light grey. The high protection standard IP56 and the high sound pressure level of the horn speakers are ideal for industrial applications.

Please consider the following features:

- The complete construction of the horn speakers series has the ultimate protection grade, IP 56.
- The 2-pole connection cable (flexible hose line) is led through a waterproof PG-screw joint.
- The 6-step impedance is switchable with a screwdriver at the rear side of the unit.
- The horn speaker system is constructed to give an outstanding high sound pressure and best sound quality reproduction. The sound pressure is dependent on the different models and the particular impedance change-over.

Technical data	H-10TA
Load rating	10 W
Nominal impedance	20 ohms
Transformer tappings at 100V	10/5/2.5/1.25 W
Frequency range	400Hz-10KHz
SPL(@1W/m)	105 dB
Protection type	IP 56
Dimension Ø×D(mm)	Ø143×210mm
Material, Colour	ABS / RAL9013

Technical data	H-15TA	H-30TA
Load rating	15 W	30 W
Nominal impedance	20 ohms	20 ohms
Transformer tappings	15/7.5/3.75/1.85 W	30/15/7.5/3.75 W
Frequency range	400Hz-10KHz	400Hz-10KHz
SPL(@1W/m)	106 dB	108 dB
Protection type	IP 56	IP 56
Dimension Ø×D(mm)	Ø208×273mm	Ø240×303mm
Material, Colour	ABS / RAL9013	ABS / RAL9013