



**TS-809**

מק"ט: 089000

### תיאור:

מיגון חיצוני פתח צד מתכתי, כולל זרוע עם תעלת חיווט, **תקן חיצוני IP68**, מאוור ומחמם 12VDC/24VAC, המיגון בנוי מיציקה אחת ובכל זאת במשקל קל יחסית

### מאפיינים:

Type	Outdoor side open camera housing
Weatherproof	<b>IP68</b>
Material/Color	Die-casting Aluminum/Beige
Power Consumption	<ul style="list-style-type: none"> <li>• Heater AC 24 V: 6 W (250 mA)</li> <li>• Heater AC 220 V: 5.3 W (23 mA)</li> <li>• Heater DC 12 V: 4.2 W (350 mA)</li> <li>• Blower: 1.68 W (140 mA)</li> </ul>
LAN Interface	RJ-45 × 2 (PoE in/data output) for PoE model ( <b>Optional</b> )
Appearance Size (W × H × L)	145 × 109 × 406 mm
View Area (L × W)	92 × 76 mm
Suitable Camera Size (W × H × L)	<ul style="list-style-type: none"> <li>• 100 × 65 × 300 mm (empty housing)</li> <li>• 100 × 65 × 220 mm (with heater/blower)</li> <li>• 100 × 65 × 200 mm (with heater/blower/PoE module) (<b>Optional</b>)</li> </ul>
Heater Control	On at 15 °C, off at 25 °C (optional)
Blower Control	On at 40 °C, off at 30 °C (optional)
Environmental Operation Temperature	-40 to 60 °C
Temper Glass Thickness	2 mm
Bracket (Optional)	Die-casting cable management bracket, TSAM1500 or TSAM1100 (optional)
Packing	6 pcs/ctn; 4.3 cuft
Unit N.W, G.W.	3.6 kg, 3.8 kg
Certifications	CE, FCC, RoHS

\*Design and specifications are subject to change without prior notice.

